



MODEL	A	B	C	STATIC TANGENTIAL FORCE @ FULL LINING
9001	4.25	5.37	6.5	5,000 LBS
9002	7.25	8.5	8	15,000 LBS
9003	10.25	12.87	12.5	35,000 LBS

Hydraulic Actuated Caliper Brake		Friction Lining: High Duty Woven Kevlar Lining		
		Medium Specification: Mineral Oil		
Design: Open		Piston Construction: Steel		
Housing Construction: Cast Ductile Iron		Surface Finish: Enamel Paint		
Maximum Hydraulic Pressure: 2,000 PSI		Torque In / Lbs: T = Braking Radius X Force In / Lbs		
Model Number:	9001	9002	9003	
Braking Tangential Force @ 2000 PSI:	5000 lbs.	15000 lbs.	35000 lbs.	
Corresponding Rotors:	16", 24" Diameter .500" Thick	16", 30, 24" Diameter 1.000" Thick	36", 42" Diameter 1.500" Thick	
Medium Volume:	.75 CU Inches	2.5 CU Inches	7 CU Inches	
Friction Lining Area:	22 Sq Inches	62 Sq Inches	140 Sq Inches	
Wearable Lining Volume:	4 Cu Inches	15 Cu Inches	40 Cu Inches	
Port Size:	SAE AS5202-4	SAE AS5202-6	SAE AS5202-8	
Weight:	25 lbs	95 lbs	260 lbs	