



MODEL	SAB112	SAB212	SAB116	SAB216
A	14	14	18	18
B	5.75	6.781	6.5	7.5
C	16.5	16.5	20.25	20.25
D	16.003	16.003	19.753	19.753
E	.188	.188	.188	.188
F	.750	.750	1	1
G MAX. BORE	2.875	2.875	3.875	3.875
H	2.50	3.125	2.75	3.625
I	5.25	6.3	5.5	6.5
MOUNTING HOLES	.65 DIA. 8 PLCS. 15.250 BCD	.65 DIA. 8 PLCS. 14.000 BCD	.53 DIA. 8 PLCS. 18.875 BCD	.53 DIA. 8 PLCS. 18.875 BCD
RELEASE PORT	1/4-18, NPT	1/4-18, NPT	1/2-14, NPT	1/2-14, NPT

SAB SERIES SPRING APPLIED / AIR RELEASED BRAKE SPECIFICATIONS

MODEL	SAB112	SAB212	SAB116	SAB216	
TORQUE (IN-LB)	NEW	18000	35000	39000	75000
	WORN	13500	26000	29000	56000
RELEASE PRESSURE	75 PSI	75 PSI	75 PSI	75 PSI	
LINING AREA (IN ²)	160	320	275	550	
HEAT CAPACITY (FT-LB)	170,000	260,000	270,000	415,000	
MAX RPM	1800	1800	1800	1800	
WEIGHT LBS.	185	225	305	375	